

Motor Run Capacitors

Dual Section Motor Run Capacitors

Dual section run capacitors are used primarily to serve two microfarad applications. They can, however, by making various combinations of parallel connections, be used to obtain many other microfarad ratings.



12841

Features:

- Non-PCB capacitors
Physical interrupter makes our capacitors safe
- Perfect for general replacements
- Capacitor accessories – see page J-7
- UL and CSA listings available

DUAL SECTION 370 VOLT OVAL				
JARD NO.	MICROFARAD	CASE HEIGHT INCHES	WIDTH INCHES	DEPTH INCHES
12841	15/3	2.38	2.81	1.81
12956	15/4	2.38	2.81	1.81
12957	15/5	2.38	2.81	1.81
12958	15/10	2.38	2.81	1.81
12959	17.5/4	2.63	2.81	1.81
12960	17.5/5	2.63	2.81	1.81
12961	20/3	2.38	2.81	1.81
12962	20/4	2.38	2.81	1.81
12963	20/5	2.38	2.81	1.81
12864	20/10	2.38	2.81	1.81
12964	20/15	2.38	2.81	1.81
12842	25/3	2.38	2.81	1.81
12965	25/4	2.38	2.81	1.81
12966	25/5	2.38	2.81	1.81
12843	25/7.5	2.63	2.81	1.81
12832	25/8	2.63	2.81	1.81
12867	25/10	2.38	2.81	1.81
12833	25/15	2.38	2.81	1.81
12844	30/3	2.38	2.81	1.81
12845	30/4	2.38	2.81	1.81
12969	30/5	2.38	2.81	1.81
12846	30/7.5	2.38	2.81	1.81
12847	30/10	2.38	2.81	1.81
12848	35/3	2.63	2.81	1.81
12971	35/4	2.38	2.81	1.81
12972	35/5	2.38	2.81	1.81
12849	35/7.5	2.38	2.81	1.81
12850	35/10	2.38	2.81	1.81
12851	40/3	3.00	2.81	1.81
12858	40/4	2.63	2.81	1.81
12871	40/5	2.38	2.81	1.81
12852	40/7.5	2.63	2.81	1.81
12834	40/10	3.00	2.81	1.81
12874	45/5	2.63	2.81	1.81
12853	45/7.5	2.63	2.81	1.81
12836	45/10	2.63	2.81	1.81
12837	45/15	2.63	2.81	1.81
12838	50/5	2.63	2.81	1.81
12854	55/5	3.75	2.81	1.81
12855	55/7.5	2.63	2.81	1.81
12839	60/5	2.63	2.81	1.81
12856	60/7.5	2.63	2.81	1.81
12857	60/10	3.75	2.81	1.81
12859	65/5	3.00	2.81	1.81
12863	80/5	3.38	2.81	1.81
12817	80/7.5	3.38	2.81	1.81

DUAL SECTION 370 VOLT ROUND			
JARD NO.	MICROFARAD	CASE HEIGHT INCHES	DEPTH INCHES
12701	15/3	3.13	2.00
12702	15/4	2.13	2.00
12703	15/5	2.13	2.00
12704	15/10	2.13	2.00
12705	17.5/4	2.13	2.00
12706	17.5/5	3.13	2.00
12707	20/4	2.13	2.00
12760	20/5	2.13	2.00
12716	20/7.5	2.63	2.00
12708	20/10	2.13	2.00
12709	20/15	3.13	2.00
12711	25/3	2.13	2.00
12875	25/4	2.13	2.00
12761	25/5	2.13	2.00
12762	25/7.5	2.13	2.00
12713	25/10	2.13	2.00
12720	30/3	2.13	2.00
12763	30/4	2.13	2.00
12764	30/5	2.13	2.00
12724	30/7.5	2.13	2.00
12728	30/10	3.13	2.00
12939	30/15	3.63	2.00
12730	35/3	2.13	2.00
12731	35/4	2.13	2.00
12766	35/5	2.13	2.00
12735	35/7.5	2.13	2.00
12738	35/10	2.13	2.00
12739	40/3	2.75	2.00
12767	40/4	2.75	2.00
12878	40/5	2.75	2.00
12768	40/7.5	2.75	2.00
12746	40/10	2.75	2.00
12747	45/3	2.75	2.00
12947	45/4	2.75	2.00
12769	45/5	2.75	2.00
12749	45/7.5	2.75	2.00
12750	45/10	2.75	2.00
12753	50/3	2.75	2.00
12755	50/5	2.75	2.00
12825	50/7.5	2.75	2.00
12757	50/10	2.75	2.00
12893	55/5	2.75	2.00
12894	55/7.5	2.75	2.00
12967	55/10	2.75	2.00
12976	60/3	2.75	2.00
12895	60/5	3.13	2.00
12896	60/7.5	2.75	2.00
12865	60/10	2.75	2.00
12742	65/5	3.13	2.00
12953	70/5	3.13	2.00
12954	70/7.5	3.13	2.00
12955	70/10	3.13	2.00
12744	75/5	3.13	2.00
12946	75/7.5	3.13	2.00
12984	75/10	3.13	2.00
12897	80/5	3.88	2.00
12819	80/7.5	3.88	2.00
12824	80/10	3.88	2.00
12722	80/12.5	3.88	2.00
12829	85/5	3.88	2.00
12756	85/7.5	4.75	2.00
12922	85/10	3.88	2.00

*Capacitors may be put in different case sizes occasionally, but will not be larger than those stated.

Base Dimensions on page J-5